



## Pundit Ultrasonic PD8050

Consolidated power in a single device for structural imaging, object and defect detection with ultrasound pulse echo



### Efficiency

Have the power of the Pundit 200 PE, Pundit 250 Array and PD8000 with a single device. Enhanced wireless inspections with on-site, 2D, heatmap and high-resolution 3D imaging



### Innovation

Experience the lightest, yet most intelligent pulse echo structural imaging device available on the market. Powered by ever-evolving software with AI and AR, to expand your inspection capabilities



### Productivity

Unbeatable productivity ensured by AI assisted positioning and data interpretation, real-time feedback of probe controls, immediate data visualization and easy report creation



## Software / Workspace App

<b>Display Unit</b>	Any compatible Apple® iPad (iOS 11.0 and higher) <sup>1</sup>
<b>Workspace Integration</b>	App synchronization Share via URL Automatic logbook Raw data export HTML export Instant report generation
<b>Special Features</b>	High definition focus view Macro view – variable frequency and voltage Wide panoramic B-scan Augmented Reality 3D view AI-assisted positioning AI-assisted feature interpretation Image stabilizer
<b>Display Unit Specs<sup>2</sup>:</b>	Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID
<b>Display Unit Sensors<sup>3</sup>:</b>	LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer Built-in GPS/GNSS

1. Recommendation: The newest models enhance performance, number of sensors and optional capabilities.

2, 3. Depending on iPad model



## Processing Unit / Sensor

<b>Applications</b>	Void and delamination detection Bonding assessment Thickness measurement Honeycombing detection Fiber concrete Concrete hit prevention Imaging of closely spaced rebars
<b>Bandwidth</b>	20 - 80 kHz
<b>Technology</b>	Multi-channel Ultrasonic Pulse Echo
<b>Measuring Resolution</b>	1 us
<b>Pulse Voltage</b>	±50 to ±150 V (UPE)
<b>Receiver Gain</b>	1 to 10'000 (0 to 80 dB)
<b>Report Generation</b>	Cloud synchronization Share via URL Cloud-enabled logbook Cloud-based raw data export Cloud-based HTML export Cloud-based report generation
<b>Measurement Modes</b>	Line scan Stripe Scan Grid Scan
<b>Measuring Range</b>	Up to 2 m / 6.6 ft depending on concrete quality
<b>Review modes</b>	A-scan (incl. envelope) B-scan (Line view) C-scan (Time-Slice view) Heat map (depth) Heat map (pulse velocity)
<b>Battery</b>	Battery pack, 6x AA (NiMH), flight-safe
<b>Display</b>	Any compatible Apple® iPad (iOS 11.0 and higher) <sup>1</sup>
<b>Memory</b>	Apple® iPad specified
<b>Connections</b>	Encrypted Wi-Fi connection to Apple® iOS tablet USB port for Wi-Fi module USB-C for Wi-Fi restricted areas

SWISS  MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

[www.screeningeagle.com](http://www.screeningeagle.com)

Request a quote

